

IN THE SPECIFICATION

Please amend the specification as follows:

Replace the paragraph on page 2, line 15 of the specification with the following:

Figs. 7a-7d shows the operation of this second embodiment,

Replace the paragraph on page 2, between lines 17-18 of the specification with the following:

Figs. 9a-9c shows how the electric connections are realized by this second embodiment.

Replace the second paragraph on page 4, between lines 15-17 of the specification with the following:

Figs. 7a-7d shows the operation of this second embodiment. The various ~~references a, b, c and d~~ figures 7a-7d show the various positions that the first part 205 of the housing can take up relative to the second part 250.

Replace the third paragraph on page 4, between lines 18-21 of the specification with the following:

~~At "a"~~ Fig. 7a shows the device ~~is~~ in closed position. It is maintained in this position by the spring 260 which acts on a stop 280 provided in part 205. This is shown by the V linked with each of said references. This figure shows in more detail the operation of the springs 260 and 261 which cooperate with the stop 280.

Replace the fourth paragraph on page 4, between lines 22-24 of the specification with the following:

~~At "b"~~ Fig. 7b shows the button 265 ~~is being~~ pressed. A press on this button releases the spring from the stop. The spring assembly 225 separates the part 250 from part 205. This release of the assembly 225 is clearly visible in this Fig. 7b.

Replace the fifth paragraph on page 4, between lines 25-26 of the specification with the following:

~~At "c"~~ Fig. 7c shows that this release is stopped by the second latch 261 which coincides with the stop 280.

Replace the sixth paragraph on page 4, between lines 27-28 of the specification with the following:

~~At "d",~~ Fig. 7d shows that, if the button 265 is pressed again, it is possible to separate the two housing parts 205 and 250.

Replace the last paragraph on page 4, between lines 31-32 of the specification with the following:

Figs. 9a-9c shows how the electrical connections are ensured in this second embodiment.

Replace the first paragraph on page 5, between lines 1-3 of the specification with the following:

~~At "a" in this Fig.~~ In Fig. 9a, the two parts 205 and 250 are represented separated from each other so as to show an assembly of conductors 300 which forms tracks arranged on part 205.

Replace the second paragraph on page 5, between lines 4-8 of the specification with the following:

~~At "b" is shown~~ Fig. 9b-9c better show how the connection piece 255 performs its function. It is provided with conductors 290 formed by a bulging part intended to make contact with the assembly of conductors 300 and by a side part to ensure the contacts with

the housing part 250. For this purpose, a housing 300 is provided, which has contacts for the electric connections of the side parts of the conductors 290.